



1961-600 220-240V 2800 HF 840 120°

For kitchens, galleys, pantries and provision stores, where there are strict hygiene rules. According to rules of USPH (U.S.Puplic Health) and to rules of maritime classification societies, additional VDE and IEC/EN.

Item Number	1961317201
GTIN	4036538594779
Stock status	A



Technical specifications

Certificates

Marine Approved	True
-----------------	------

Technical Data

Minimum ambient temperature (°C)	-25
Maximum ambient temperature (°C)	45
IP classification	67

Light Technical Data

Light source	LED
Lumen out (lm)	2526
Lumen value supplied light source (lm)	2800
Lumen per Watt (lm/W)	140
Lamp colour temp (K)	4000
CRI Colour rendering index	>80
MacAdam step	3
Energy class light source	C
Light source included	True

Driver / Ballast

Type of LED Driver	HF: Non dimmable
Number of Driver	1

Electrical Data

Mains current	0,09
EMC Category	EMC1: EMC B – IEC 60533 Bridge and Open deck
Minimum Voltage -10% (VAC)	220
Maximum voltage +10% (VAC)	240
Minimum frequency -5% (Hz)	50
Maximum frequency +5% (Hz)	60
Main Feed DC (V) Min	180
Main Feed DC (V) Max	270
Total consumption (W)	18
Number of luminaires on a 10A MCB type B	13
Number of luminaires on a 10A MCB type C	22
Number of luminaires on a 16A MCB type B	22
Number of luminaires on a 16A MCB type C	37
Power factor	0.86

Housing

Main body material	Stainless steel 304
Body colour	WH - White
Main body colour name	White

Dimensions

Length (mm)	723
Width (mm)	183
Height (mm)	83
Net weight (kg)	2.944

Cable Inlet

Number of blind plugs	2
Max cable diameter (mm)	12

Logistic Data

Item gross weight (kg)	3.2
------------------------	-----

Illustrations



