



# 1961 KIT-1200 LED 220-240V 5500 HF 840 120°

For kitchen there are strict hygienic rules. This has been taken into account when designing this luminaire. The soft contours enable easy and rapid cleaning. This conversion kits are for 1961 - 2800lumen and 5500lumen.



Item Number	8196155500
GTIN	4036538594748
Stock status	C



## Technical specifications

### Certificates

Marine Approved	True
-----------------	------

### Technical Data

Minimum ambient temperature (°C)	-25
Maximum ambient temperature (°C)	45

### Light Technical Data

Light source	LED
Lumen out (lm)	4801
Lumen value supplied light source (lm)	5500
Lumen per Watt (lm/W)	141
Lamp colour temp (K)	4000
CRI Colour rendering index	>80
Energy class light source	C
Light source included	True

### Driver / Ballast

Type of LED Driver	HF: Non dimmable
--------------------	------------------

### Electrical Data

Mains current	0.160
Minimum Voltage -10% (VAC)	220
Maximum voltage +10% (VAC)	240
Minimum frequency -5% (Hz)	50
Maximum frequency +5% (Hz)	60
Main Feed DC (V) Min	180
Main Feed DC (V) Max	270
Total consumption (W)	34
Number of luminaires on a 10A MCB type B	13
Number of luminaires on a 10A MCB type C	21
Number of luminaires on a 16A MCB type B	21
Number of luminaires on a 16A MCB type C	35

### Housing

Main body material	Stainless steel 304
Body colour	WH - White
Main body colour name	White

### Dimensions

Length (mm)	1240
Width (mm)	147
Height (mm)	57
Net weight (kg)	2.024

### Logistic Data

Item gross weight (kg)	2.2
------------------------	-----

## Illustrations

