



MIR KIT-1200 (M) G2 5000 HF EB3/S 840 FR/PC IP66/67 Incl. Battery

E3/S or EB3/S means that this item has a built-in emergency light for up to 3 hours duration. EB/S - stands for External Battery and Standard Emergency. The number 3 indicates the emergency time in hours. It is supplied with a standard emergency controller that needs manual testing according to European emergency light standards.

Item Number	MIR106500
GTIN	7054131065004
Stock status	Α



Technical specifications


Certificates	
Marine Approved	True
EX zone	No Ex
Technical Data	
Minimum ambient temperature (°C)	-20
Maximum ambient temperature (°C)	45
IP classification	66/67
Light Technical Data	
Light source	LED
Lumen out (Im)	5168
Number of lamps	1
Lumen per Watt (Im/W)	153
Lamp colour temp (K)	4000
CRI Colour rendering index	>80
Light distribution up %	2
Light distribution down %	98
MacAdam step	3
Energy class light source	С
Light source included	True
Driver / Ballast	
Type of LED Driver	HF: Non dimmable
Number of Driver	1
Lifetime	
L80 Median useful life LED Ta45 (hr)	100 000


Electrical Data	
EMC Category	EMC1: EMC B – IEC 60533 Bridge and Open deck
Leakage current (mA)	0.3
Minimum Voltage -10% (VAC)	220
Maximum voltage +10% (VAC)	240
Minimum frequency -5% (Hz)	50
Maximum frequency +5% (Hz)	60
Total consumption (W)	37
Number of luminaires on a 10A MCB type B	6
Number of luminaires on a 10A MCB type C	12
Number of luminaires on a 16A MCB type B	12
Number of luminaires on a 16A MCB type C	24
Emergency	
Type of emergency	Standard battery backup
Duration in battery mode	(hrs) 3
Charging power consumption (Emg) (W)	otion 1.5
Optic	
Optic	FR/PC - Frosted diffuser in polycarbonate
Material of diffuser	Polycarbonate



Housing	
Body colour	WH - White
Main body colour name	White
Dimensions	
Length (mm)	1250
Net weight (kg)	3.68
Logistic Data	
J	
Item gross weight (kg)	4
Remarks	
Includes: Battery, battery plug, gear tray, diffudiffuser clips	iser and

Illustrations





MULTI-1200 G2